

SCENIC 2710

27x10W RGBW 4in1 LED PAR with 25° beam for indoor use

The Centolight **Scenic 2710** PAR Light is a versatile high-performance lighting fixture tailored for dynamic and creative lighting applications. Featuring 27 x 10W 4-in-1 RGBW LEDs, it delivers bright and vibrant colors with a beam angle of 25°, making it ideal for stage performances, events, and architectural lighting. With a light source lifespan of up to 50,000 hours, the Scenic 2710 ensures reliable, long-term operation.

The fixture offers a wide range of operation modes, including DMX512, Auto, Master/Slave, and Sound, providing flexibility for both standalone and integrated setups. Control is made simple with two DMX channel modes (8CH A and 8CH B), allowing precise adjustments for color mixing, effects, and performance synchronization.

Advanced features include a strobe effect with a speed range of up to 20Hz and a smooth linear dimmer for seamless transitions. These capabilities enable remarkable effects, from subtle fades to high-energy flashes, enhancing the visual impact of any production.

Designed for user convenience and professional performance, the **Scenic 2710** combines durability with creative control, making it an essential tool for lighting designers, event planners, and entertainment professionals.



PRODUCT DETAILS

Key features

Ideal for stage performances, events, and architectural lighting

Light Source	27 x 10W RGBW 4in1 LEDs
Beam Angle	25°
2 DMX Channel modes (8CH A and 8CH B)	
Electronic strobe with adjustable speed	
Smooth dimming function	
Dynamic color transitions for mood and atmosphere in any setting	
Auto, Master/Slave, DMX512 and Sound Control modes	
Durable, heat-resistant lens	
Fin+Fan heat dissipation cooling system	

Specifications

Light Source	27x10W 4-in-1 RGBW LEDs
Light Source	Lifespan 50.000 hours
Beam Angle	25°
Antistatic	Up to 2000V HBM
Lens material	High temperature resistant PC+PMMA
Body material and coating	Aluminum alloy, fine-sand paint
Cooling System	Fin+Fan heat dissipation
Control Mode	DMX, Master/Slave, Auto, Sound
DMX Channels	8CH A /8CH B Modes
DMX Connectors	3-pin XLR Input/Output
Power Connectors	Powercon Input/Output
IP Grade	IP20
Input Voltage	AC100V-240V (50/60Hz)
Power Consumption	200W
Ambient Temperature	0° - 35°C
Fixture Dimensions with brackets installed (WxDxH)	274 x 281 x 216 mm(10.78 x 11.06 x 8.50 in.)
Packing Dimensions (WxDxH)	265 x 265 x 340 mm(10.43 x 10.43 x 13.38 in.)
Product Weight	2.8 kg – 6.17 lbs.
Package Weight	3.6 kg – 7.94 lbs.